Artemide

Ð¢Ð•Ð¥Ð•Ð˜Ð§Ð•Ð¡ÐšÐ˜Ð• Ð”Ð•Ð•Ð•Ð«Ð• ÐŸÐ ÐžÐ”Ð£ÐšÐ¢Ð•

Tian Xia 500 - Fluo

Ð”Ð¯Ð—Ð•Ð™Ð•

Carlotta de Bevilacqua
2008

ÐœÐ•Ð¢Ð•Ð Ð¾Ð•Ð›Ð«

Polished aluminium, thermoplastic resin, translucent film, polyester

ÐžÐŸÐ¯Ð¡Ð•Ð•Ð¯Ð•

With a diameter of 50cm is the size reduced version of the classic model of Tian Xia. Mirror-treated finish polished aluminium structure; thermoplastic resin diffuser with translucent film mirrorfinish. Blue filter in polyester.

Dimmer included.

Ð'Ð¸Ð´ Ñ•Ð²ÐµÑ‚Ð¾Ð²Ð¾Ð¾ Ð¿Ð¾Ñ‚Ð¾Ð¿Ð°

Diffused,direct,indirect

IP 20

+ –

Ð¢Ð•Ð¥Ð•Ð˜Ð§Ð•Ð¡ÐšÐ˜Ð• Ð”Ð•Ð•Ð•Ð«Ð•

Ð¥Ð•Ð Ð•ÐšÐ¢Ð•Ð Ð˜Ð¡Ð¢ÐšÐ˜

Ð•Ð°Ð¸Ð¼ÐµÑ½Ð¾Ð²Ð°Ð½Ð¸Ðµ	Tian Xia 500 - Fluo
Ð¿Ñ€Ð¾Ð´Ñƒ†Ð¸Ð¸	
ÐšÐ¾Ð´	**A246000**
Ð¦Ð²ÐµÑ‚	Polished aluminium
ÐœÐ°Ñ‚ÐµÑ€Ð¸Ð°Ð»	Polished aluminium, thermoplastic resin, translucent film, polyester
Ð¡ÐµÑ€Ð¸Ð¯	Design
ÐžÐ°Ñ€ÑƒÐ¶Ð°Ñ‰Ð°Ñ• Ñ•Ñ€ÐµÐ´Ð°Ñ‚ÐµÐ½Ð½Ð½ÐµÐµ	

ÐžÐŸÐ¢Ð˜ÐšÐ•

Ð'Ð¸Ð´ Ñ•Ð²ÐµÑ‚Ð¾Ð²Ð¾Ð¾ Ð¿Ð¾Ñ‚Ð¾Ð¿Ð°: Diffused,direct,indirect

Ð Ð•Ð—ÐœÐ•Ð Ð«

Ð'Ñ‹Ñ•Ð¾Ñ‚Ð°	(cm) 29
Ð"Ð¸Ð°Ð¼ÐµÑ‚Ñ€	(cm) 50
Ð"Ð¸Ð°Ð¼ÐµÑ‚Ñ€ Ð±Ð°Ð·Ñ‹	(cm) 30
ÐœÐ°Ñ•Ð¸Ð¼Ð°Ð»ÑŒÐ½Ð°Ñ• Ð²Ñ‹Ñ•Ð¾Ñ‚Ð° Ð¾Ñ, Ð¿Ð¾Ñ‚Ð¾Ð»Ð°Ð°	(cm) 200
Ð¤Ð¾Ñ€Ð¼Ð°Ñ‚ Ð¾Ñ€Ð¸Ð¸Ð½Ð°Ð»	

Ð¤Ð•Ð¢Ð•Ð Ð«

ÐšÐ°Ñ‡ÐÑ€Ð¾	FLUO
ÐšÐ¾Ð»Ð¸Ñ‡ÐµÑ•Ñ‚Ð²Ð¾	2
Lbs:	Tc-tel
Ð'Ð°Ñ‚Ñ	42
Ð¦Ð°Ð¾Ð¼Ð»ÑŒ	Gx24q-4
Ð¢Ð¸Ð¿	Fsm
Ð¦Ð²ÐµÑ‚Ð¾Ð¿Ð¿Ð¿ÐµÑ€Ð´Ð°Ñ‡Ð°	
Ð¦Ð²ÐµÑ‚Ð¾Ð²Ð°Ñ• Ñ‚ÐµÐ¼Ð¿ÐÐµÑ€Ð°Ñƒ€Ð° (K):	
ÐŸÑ€Ð¾Ð´Ð¾Ð»Ð¶Ð¸Ñ‚Ð�½Ð¾Ñ•Ñ‚ÑŒ	

Ð Ð•Ð—ÐœÐ•Ð Ð«



Ð›Ð•ÐœÐŸÐ•

IP 20

+ –

Ð-Ð›Ð•ÐšÐ¢Ð Ð˜Ð§Ð•Ð¡ÐšÐ˜Ð™

ÐŸÐ:Ð•	Electronic Integrated
Ð•Ð°Ð¿Ñ€Ñ•Ð¶ÐµÐ½Ð¸Ðµ	220V-240V